

## AC325DC Switch Mode Power Supply

The Netherlands  
 ☎ +31 164 265921  
 ✉ info@deionx.com  
 🌐 www.deionx.com



www.deionx.com  
 EDI DC Powersupply AC325DC

### The AC325DC is designed to

- Stand out because of their compact design, high control accuracy, low ripple, low weight, and a significantly improved efficiency.
- The improved dynamic response of the output values which allow set point value deviations at the DC voltage output to be adjusted within milliseconds.
- And simple control features for start/stop, current and voltage control and output signals.

### Description and Use

In contrast with other electronic rectifiers, the ripple of AC315DC power supplies is constant. This result in a generate high quality direct current. The power section is installed in an enclosure made from insulating material.

### Quality Assurance

- CE marked.  
Each module is factory tested to meet strict industry standards.

### AC315DC Electrical data

Mains Voltage EU	3 x 400 VAC ± 10%, 47-63 Hz
US	3 x 460 VAC ± 10%, 47-63 Hz
Mains Current	45 A
Mains Power	31 kVA

Nominal DC Voltage	300	400	500	VDC
Nominal DC Current	84	63	50	ADC
Control Voltage	24 VDC or 230 VAC			

Efficiency	up to 90%
Ripple	< 3% referred to nominal values
Adjustment ranges	0 to 100% of nominal output
Set Voltage Value	0...10 VDC or 0/4...20 mA DC
Set Current Value	0...10 VDC or 0/4...20 mA DC
Control Accuracy	±1% referred to nominal values

Cooling	Forced air-cooled
Ambient Temperature	0 to 45 °C

Dimensions W / D / H	490 / 443 / 276 mm
Weight	42 kg
Protection grade	IP20

### Materials

The rectifier consists at more than 95% of recyclable materials. Depending on the construction the device contains the following material

### Typical Applications

- Electro Separation Technologies as:
  - Electro Dialysis (ED)
  - Electro Dialysis Reverse (EDR)
  - Electro Delonization (EDI)
- Modern electrochemical processes
- Any industrial application that requires stable DC power